











# DUPLEX WEBBING SLINGS

## Becket eyes each end



Colourcode according to DIN-EN 1492-1		Working Load Limits with 1 webbing sling					Working Load Limits with 2 webbing slings			
		straight lift	choked lift	β			straight lift up to 45°	choked lift up to 45°	straight lift 45° - 60°	choked lift 45° - 60°
				0° - 7°	7° - 45°	45° - 60°				
										
		1.0	0.8	2.0	1.4	1.0	1.4	1.12	1.0	0.8
<b>WLL 1 T</b>	<b>Violet</b>	1,000	800	2,000	1,400	1,000	1,400	1,120	1,000	800
<b>WLL 2 T</b>	<b>Green</b>	2,000	1,600	4,000	2,800	2,000	2,800	2,240	2,000	1,600
<b>WLL 3 T</b>	<b>Yellow</b>	3,000	2,400	6,000	4,200	3,000	4,200	3,360	3,000	2,400
<b>WLL 4 T</b>	<b>Grey</b>	4,000	3,200	8,000	5,600	4,000	5,600	4,480	4,000	3,200
<b>WLL 5 T</b>	<b>Red</b>	5,000	4,000	10,000	7,000	5,000	7,000	5,600	5,000	4,000
<b>WLL 6 T</b>	<b>Brown</b>	6,000	4,800	12,000	8,400	6,000	8,400	6,720	6,000	4,800
<b>WLL 8 T</b>	<b>Blue</b>	8,000	6,400	16,000	11,200	8,000	11,200	8,960	8,000	6,400
<b>WLL 10 T</b>	<b>Orange</b>	10,000	8,000	20,000	14,000	10,000	14,000	11,200	10,000	8,000
<b>WLL 12 T</b>	<b>Orange</b>	12,000	9,600	24,000	16,800	12,000	16,800	13,440	12,000	9,600

Higher rated slings available upon request

### Type

-Double ply polyester webbing sling with reinforced lifting eyes.

### Technical specifications

-Colour coded according to DIN-EN 1492-1.

### Characteristics

-Low elongation.

### Norms

-According to Machine Directive 98/37/EC.



### CAUTIONS...

- Do not exceed Working Load Limit.
- Prevent shock-loading.
- When selecting a sling it is very important to consider the angles at which the sling will be used.
- Slings are subject to cutting when lifting items with sharp edges. In this case always use wear sleeves.
- Do not use a damaged sling.
- Never make knots in a sling.
- Never drag a sling from underneath a load that is resting on it.
- Chemical active environments can affect the strength of slings.
- Operating temperature range: -40 C to +100 C.
- Inspect slings weekly or more frequently depending on sling use.
- Always store slings in a cool dry and dark place when they are not in use for prolonged periods.
- Always read and understand the operating instructions before use.



## R & G Marine & Industrial Services Limited

Units A1/A2 Brickmakers Industrial Estate, Castle Road  
Sittingbourne, Kent, ME10 3RL, UK

Tel: 44(0)1795 470430

Fax: 44(0)1795 429722

Email: [sales@randgmarine.co.uk](mailto:sales@randgmarine.co.uk) Website: [www.randgmarine.co.uk](http://www.randgmarine.co.uk)

